

# 158ML11660

3.0"

**ML121RT: LOW VOLTAGE TRANSFORMER** **MAIBU**  
**IN: 120 V - 60 Hz, 1.3A. MAX. OUT: 12 V, 121 W MAX.**

TOTAL WATTAGE NOT TO EXCEED 121 WATTS. NUMBER OF LIGHTS X WATTAGE OF EACH LIGHT = NOMINAL WATTAGE.  
 EL VATAJE TOTALE NO DEBE EXCEDER 121 VATIOS, NUMERO DE LAMPARAS X VATAJE DE CADA LAMPARA = VATAJE NOMINAL.  
 PUISSANCE TOTALE NE DOIT PAS DEPASSER 121 WATTS. NOMBRE DE LAMPES X PUISSANCE DE CHAQUE LAMPE = PUISSANCE NOMINALE.

**FOR USE WITH INTERMATIC BULBS.**  
**PARA SER UTILIZADA CON BOMBILLAS DE INTERMATIC**  
**UTILISER AVEC LES AMPOULES INTERMATIC**  
 EXM. 8 Lamps X 14 W 11Lamps X 11W 17 Lamps X 7W 30 Lamps X 4W

**For use with Intermatic outdoor low voltage landscape lighting only.**  
**INSTALL OUTDOORS ONLY AT LEAST 1 FT. ABOVE GROUND AND MORE THAN 10 FT. FROM INSIDE WALL OF SWIMMING POOLS AND SPAS. DO NOT USE WITH A DIMMER.**

**Para uso con sistema de iluminación de bajo voltaje para jardines y exteriores fabricado por Intermatic.**  
**INSTALE SOLAMENTE EN EXTERIORES POR LO MENOS A 1 PIE DEL SUELO Y A MAS DE 10 PIES DE LAS PAREDES INTERIORES DE ALBERCAS Y DE TINAS DE HIDROMASAJE. NO UTILICE CON AMORTIGUADORES DE LUZ.**

**Utiliser avec les lampes extérieures de paysage basse tension Intermatic.**  
**INSTALLER SEULEMENT À L'EXTÉRIEUR AU MOINS 1 PIED AU-DESSUS DU SOL ET À PLUS DE 10 PIEDS DU MUR INTÉRIEUR DES PISCINES ET DES SPAS.**  
**NE PAS UTILISER AVEC UN GRADATEUR.**

**INTERMATIC INCORPORATED**  
 158ML11660 MADE IN MEXICO LISTED 493R LR42620 US

2.88"

**NOTES:**

- 1. ALL MARKINGS ARE TO BE AS PER INTERMATIC APPROVED ARTWORK, AND TO BE CENTRALLY LOCATED ON LABEL.**

D75

**APPROVED MATERIAL:**

- 1. WHITE VINYL WITH PERMANENT PRESSURE SENSITIVE ADHESIVE BACKING. (.005" THICK)**
- 2. CLEAR POLYESTER FILM (LAMINATE) WITH PERMANENT ACRYLIC ADHESIVE (1 MIL THK)**

**SEE B/M FOR ALL PART NUMBERS & QUANTITIES**

|  |                        |         |       |   |                                   |             |             |     |
|--|------------------------|---------|-------|---|-----------------------------------|-------------|-------------|-----|
|  |                        |         |       | DR: SRB 2/23/2004   | ITEM                              | PART NUMBER | DESCRIPTION | QTY |
|  |                        |         |       | ORIG:   | <b>INTERMATIC INCORPORATED</b>    |             |             |     |
|  |                        |         |       | CHKD: JAP 2/23/2004   | NAME: INST SHT - DOOR, ML121RT    |             |             |     |
|  |                        |         |       | SCALE: FULL   | MATL: APPROVED MATERIAL           |             |             |     |
|  |                        |         |       | <b>APPROVED</b>   | FINISH: <b>BLACK PRINTING INK</b> |             |             |     |
| 1  | RELEASED TO ELEC. DATA |         |       | JAP 2/23/2004   | HEAT TREAT                        |             |             |     |
| LET  | REVISION               | DATE/BY | MODEL | SUPERSEDES  |                                   |             |             |     |
| <b>DIMENSIONING SYSTEM:</b>  |                        |         |       | <b>DIM TOL.:</b>  |                                   |             |             |     |
| ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED-METRIC DIMS IN BRACKETS IF DUAL DIMENSIONING |                        |         |       | DECIMALS (UNLESS OTHERWISE SPECIFIED) - TWO PLACE (.00)± .015 - THREE PLACE (.000)± .005<br>ANGLES ±30 MINUTES - ALL DIMENSIONS MUST BE MET BEFORE PLATING. |                                   |             |             |     |